

User Information

37D
Issue 6 Date: 18.05.2026




PROTECTIVE TROUSERS STYLE PG3/A AND PG3/B



TECHNICAL

This garment has been designed to give a specified level of protection against accidental contact with blades and similar sharp implements. In the design of this garment due respect has been paid to the basic health and safety requirements laid out in PPE Regulation (EU) 2016/425 as brought into UK Law and amended. The garment has been tested in accordance with EN 388: 2016.


Tested in accordance with EN388:2016  X- Not tested		Level	Minimum level	Maximum level
	Abrasion resistance	2	0	4
	Blade cut resistance	X	0	5
	Tear resistance	4	0	4
	Puncture resistance	4	0	4
	TDM Cut resistance	C	A	F

Standard Sizes Leg Lengths: Short 74cm (29") Regular 79cm (31"), Tall 84cm (33").

Ladies Sizes Leg lengths: Short 69cm (27"), Regular 74cm (29"), Tall 79cm (31"), XTall 84cm (33").

Special sizes available on request.

STANDARD SIZES:		LADIES SIZES:		
Waist Order Size Inches:	Waist Size CM:	Order Size:	Waist in Inches:	Waist in CM:
30"	76	6	26"	66
32"	81	8	28"	71
34"	86	10	30"	76
36"	91	12	32"	81
38"	97	14	34"	86
40"	102	16	36"	91
42"	107	18	38"	97
44"	112	20	40"	102
46"	117	22	42"	107
48"	122	24	44"	112



WARNING: The garment is **CUT RESISTANT** not **CUT PROOF**. The actual conditions of use cannot be simulated and it is the responsibility of the user, not the manufacturer, to determine the garment's suitability for the intended use. The garment is sold without warranty expressed or implied. No warranty or representation is made as to the product's ability to protect the user from injury or death. The user assumes that responsibility. Do not use next to moving machinery.

USE.

These garments are for the intended use within the glass industry. New and used garments should be thoroughly inspected before use to ensure no damage is present.

THESE GARMENTS ARE DESIGNED TO GIVE PROTECTION TO THE OUTER SIDE OF THE LEG ONLY. WHERE THERE IS ANY RISK OF CUTS TO THE INSIDE OF THE LEG THE GARMENT MUST BE WORN IN CONJUNCTION WITH A SUITABLE CUT RESISTANT APRON SUCH AS DALE TECHNICHE'S STYLE PG2/A.

GARMENT CARE.

The test results for the garment were achieved after 5 washes. Stored garments should be kept in their original packaging in a dry place away from heat and direct sunlight. Hand or machine wash in water not exceeding 40°C using a good proprietary washing powder or detergent. **Do not use bleach.** Line dry or dry flat. **Do not tumble dry.** The garment can be ironed with a medium iron if necessary. Failure to observe the above instructions and aggressive or repeated washing may affect the mechanical or EN388 performance of the garment.

REPAIR. Do not repair this garment.

Notified Body.

EU type examination performed by SATRA Technology Europe, Bracetown Business Park, Clonee, D15 YN2P Ireland. Notified Body number 2777.

Approved body for Type Approval: SATRA Technology Centre Ltd (AB 0321), Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, UK.

EU certificates of conformity can be accessed by logging on to www.daledoc.co.uk

REINFORCED AREAS.

PG3/A

Front

Back



Reinforced areas

PG3/B

