

Throstle Nest Mill, Leeds Road, Nelson, Lancashire, England BB9 7QZ.

Phone - 01282 696214.

www.daledoc.co.uk - www.jaysracewear.co.uk salesoffice@dale-techniche.co.uk



## Care & Usage Sheet Issue 2 Date: 29.04.2021 CHIEFTAIN® GARMENT PG1/S SWEATSHIRT.

**<u>TECHNICAL:</u>** This garment has been designed to give a specified level of protection against accidental contact with blades and similar sharp implements.

Tested in accordance		Level	Minimum	Maximu
with			level	m level
EN388:2016	Abrasion resistance	1	0	4
	Blade cut resistance	5	0	5
	Tear resistance	4	0	4
	Puncture resistance	2	0	4
	TDM Cut resistance	В	Α	F
1542B				



Fit according to chest size

SWEATS/POLOS											
SIZE	XS	S	М	L	XL	2XL	3XL	4XL	5XL	6XL	7XL
CHEST (INCHES)	36"	38"	40"	42"	44"	46"	48"	50"	52"	54"	56"
CHEST (CM)	90cm	95cm	100cm	105cm	110cm	115cm	120cm	125cm	130cm	135cm	140cm
HEIGHT (CMS)	153-190	153-190	153-190	153-190	153-190	153-190	153-190	153-190	153-190	153-190	153-190



**WARNING:** The garment is <u>CUT RESISTANT</u> not **CUT PROOF.** Garments should not be worn when there is a risk of entanglement by moving parts. The actual conditions of use cannot be simulated and it is the responsibility of the user, not the manufacturer, to determine the garment's suitability for the intended use. The garment is sold without warranty expressed or implied. No warranty or representation is made as to the product's ability to protect the user from injury or death. The user assumes that responsibility.

Please note – Kevlar® materials used in the garment change colour with continued exposure to light from bright yellow when new to a brownish colour. This does not affect the cut resistant properties of the garment.

**GARMENT CARE:** Stored garments should be kept in their original packaging in a dry place away from heat and direct sunlight. The fabric from which your Chieftain garment is made contains materials that are sensitive to temperatures above 100°C. **Do not let the garment come into contact with flame or very hot surfaces.** 

New and used garments should be thoroughly inspected, especially after washing, to ensure no damage is present. Do not fill the washing machine more than 2/3 full.

Do not use bleaches or caustic washing agents as these will damage the Kevlar® fibres. Hand or machine wash in water not exceeding 40°C using a good proprietary washing powder or detergent, with low or no optical whitener and oxidant content, such as Dreft Automatic, Wisk or similar. Do not dry clean. Line dry or dry flat. Do not tumble dry. Do not iron.

Failure to observe the above instructions and aggressive or repeated washing may affect the mechanical or EN388 performance of the garment.

**REPAIR:** Do not repair this garment using fabrics other than fabrics of similar construction and blade cut resistant properties. If in doubt, consult the manufacturer before attempting repair,

## **Notified Body:**

## Notified Body for CE marking:

BTTG® Notified Body 0338, BTTG, Manchester, M17 1EH, performed the EU type-examination (Module B), which is now held by Shirley®, Notified Body 2895, Port Tunnel Business Park, Office 13 Unit 21, Dublin 17, ROI.

## Approved Body for UKCA marking:

BTTG® Approved Body 0338, BTTG, Manchester, M17 1EH, performed the type-examination (Module B) for UKCA approval.

Further information on this garment can be obtained from Dale Techniche Ltd. at the location shown at the top of this page. EU Certificates of Conformity can be accessed by logging on to <a href="www.daledoc.co.uk">www.daledoc.co.uk</a>.