

TECHNICAL SPECIFICATION SHEET

SINGLE LAYER, FR COVERALL - ARC1001/15

Garment conforms to:	<p>Flame retardant, anti-static, single layer coverall made from durable 220gsm fabric giving protection against the thermal effects of an electric arc.</p> <p>IEC61482-1-1: (open arc) ATPV = 9.4cal/cm². IEC61482-1-1 (2.0) ELIM 8.6cal/cm² IEC61482-1-2:2007 (arc in a box) Class 1 = 4kA IEC61482-2:2020 ISO11612:2015 (A1, B1, C1) Protection against heat and flame. EN1149-5:2018 Discharges of static electricity.</p>
Garment standard description:	<p>The garment features a high collar, comfort pleated back, elasticated waist, concealed 2 way main zip with placket and Velcro fastening, vented self-fabric cuffs with Velcro tab fastenings, 2 hip pockets, 2 cargo pockets with flaps, 2 back pockets with flaps, adjustable concealed zip closure to leg bottom, external knee pad pockets.</p> <p>Reflective tape as required.</p>
Sizes:	Sizes S to 2XL. Leg lengths short (74cm), regular (79cm) and long (84cm), Larger sizes & MTM upon request
Labels:	CE & UKCA to IEC 61482-2:2020, ENISO11612:2015, EN1149-5:2018.

Fabric:	56% para aramid, 42% meta aramid, 2% antistatic fibre, woven fabric, 220 gsm, with rip stop grid.
Colour:	Black
Conforms to:	EN ISO11612:2015 A1, B1, C1, EN 1149-3:2004 IEC61482-1-1:2009 (open arc) ATPV = 9.4cal/cm ² IEC61482-1-1 (2.0) ELIM 8.6cal/cm ² IEC 61482-1-2:2007 (arc in a box) Class 1 (4KA)
Sewing thread:	100% meta aramid.

For and on behalf of
DALE TECHNICHE LIMITED

D Emmott

Operations Manager.

