

## **TECHNICAL SPECIFICATION SHEET**

### **2 LAYER, FR LONG COAT - ARC2002/20**

Garment conforms to:	Flame retardant, antistatic, 2 layer long coat made from durable 220gsm outer fabric & 220gsm knitted rib fabric giving protection against the thermal effects of an electric arc.  IEC61482-1-1 (open arc) ATPV = 45cal/cm <sup>2</sup> IEC61482-1-1 (2.0) ELIM 42cal/cm <sup>2</sup> . IEC61482-2:2020 ISO11612:2015 (A1, B1, C1) protection against heat and flame. EN1149-5:2018 discharges of static electricity.
Garment standard description:	The garment includes, high neck, non-metallic zip with Velcro fastened placket, lower hip pockets with Velcro fastened flaps. Knitted cuffs to sleeves.  Additions: Two rows of yellow and silver tape over shoulders and around arms one row around the hem. D ring to left and right chest below tape. Elim 42cal heat seal to left hand pocket.
Sizes:	S, M, L and XL. Other sizes upon request.
Labels:	CE & UKCA to IEC61482-2:2020, ENISO11612:2015, EN1149-5:2018

Outer Fabric:	56% Meta-aramid, 42% Para-aramid, 2% antistatic fibre, woven fabric, 220 gsm, with rip stop grid.
Colour:	Black
Conforms to:	EN ISO11612:2015 A1, B1, C1, EN 1149-3:2004 IEC61482-1-1:2009 (open arc) ATPV = 9.4cal/cm <sup>2</sup> IEC61482-1-1 (2.0) ELIM 8.6cal/cm <sup>2</sup> IEC 61482-1-2:2007 (arc in a box) Class 1 (4KA)
Inner Fabric:	79% Meta-aramid, 14% FR Viscose, 5% Para-aramid, 2% antistatic fibre, knitted fabric, 220gsm
Colour:	Navy blue or Black
Conforms to:	ISO11612:2015 (A1, B1, C1), EN1149-3:2004, IEC61482-1-1:2009 (open arc) EBT50 = 9.6cal/cm <sup>2</sup> IEC61482-1-1 (2.0) ELIM = 8.2cal/cm <sup>2</sup> IEC61482-1-2:2007 (arc in a box) Class 1 (4KA)
Fabric Combination:	IEC61482-1-1:2009 (open arc) ATPV = 45cal/cm <sup>2</sup> IEC61482-1-1 (2.0) ELIM 42cal/cm <sup>2</sup>
Sewing thread:	100% meta aramid.

For and on behalf of  
**DALE TECHNICHE LIMITED**

D Emmott  
Operations Manager.



Certificate number 2322/00