

TECHNICAL SPECIFICATION SHEET

BALACLAVA – BNC969

| | |
|-------------------------------|--|
| Garment conforms to: | Balaclava giving protection against accidental contact with heat and flame, conforming to: IEC61482-1-1:2009 Open Arc ATPV = 12 cal/cm². IEC61482-1-2:2007 Arc in a box class 1. IEC61482-2:2009 ISO11612:2015 Protection against heat and flame EN1149-5:2008 Discharges of static electricity |
| Garment standard description: | Open face balaclava made from flame retardant, single sided fleece fabric. Face opening is designed so that lower part can be worn under or over the nose. The raised side of the fabric is on the inner of the balaclava. |
| Sizes | One size |
| Labels: | CE / UKCA to EN11612:2015, EN1149-5:2008 IEC61482-2:2009 |

Fabric Used

| | |
|----------------------|--|
| Product Reference: | 2770 |
| Product Description: | Knitted Fabric |
| Colour: | Black or Navy |
| Fibre Composition: | 93% Nomex, 5% Kevlar, 2% Antistatic fibre. |
| Construction: | Single sided fleece |
| Weight: | 260-280 GSM |
| Fabric conforms to | EN11612:2008 A1, B1, EN1149-3:2004 IEC61482-1-1:2009 open arc ATPV = 12cal/cm² IEC61482-1-2:2007 arc in a box class 1. |
| Sewing thread | 100% aramid |

For and on behalf of
DALE TECHNICHE LIMITED

D Emmott

Operations Manager.



Certificate number 2322/00