

## **TECHNICAL SPECIFICATION SHEET**

### **BALACLAVA – BNC969**

Garment conforms to:	Balaclava giving protection against accidental contact with heat and flame, conforming to: EN61482-1-1 ELIM = 7.3cal/cm <sup>2</sup> / ATPV = 9cal/cm <sup>2</sup> EN61482-2:2020 EN ISO11612:2015 Protection against heat and flame EN1149-5:2018 Discharges of static electricity
Garment standard description:	Open face balaclava. The face opening is designed so that lower part can be worn under or over the nose. The raised side of the fabric is on the inner of the balaclava.
Sizes	One size
Labels:	CE to EN ISO 11612:2015 A1, B1, C2, EN1149-5:2018, EN61482-2-2020

#### **Fabric Used**

Product Reference:	2770
Product Description:	Knitted Fabric
Colour:	Black or Navy
Fibre Composition:	93% Nomex, 5% Kevlar, 2% Antistatic fibre.
Construction:	Single sided fleece
Weight:	260-280 GSM
Fabric conforms to	EN ISO 11612:2015 A1, B1, C2 EN1149-3:2004 IEC61482-1-1:2019 ELIM = 7.3cal/cm <sup>2</sup> ATPV = 9cal/cm <sup>2</sup>
Sewing thread	100% aramid

For and on behalf of  
**DALE TECHNICHE LIMITED**

**D Emmott**

\_\_\_\_\_  
**Operations Manager.**



Certificate number 2322/00