

TECHNICAL SPECIFICATION SHEET

SINGLE LAYER COVERALL – ARC1001/30

Garment conforms to:	Flame retardant, antistatic single layer coverall made from Teflon coated durable 250gsm fabric giving protection against the thermal effects of an electric arc. IEC61482-1-1:2009 (open arc) ATPV = 10.5cal/cm ² IEC61482-1-2:2007 (arc in a box) Class 1. IEC61482-2:2009 ISO11612:2015 (A1, B1, C1) protection against heat and flame. EN1149-5:2008 discharges of static electricity. EN13034:2005 Type 6 low chemical protection.
Garment standard description:	The garment features a high collar, comfort pleated back, elasticated waist, and concealed 2 way main zip - placket with Velcro fastening, stretch knitted cuffs, 2 side entry pockets, adjustable concealed zip closure to leg bottom, internal knee pad pockets. Optional features – Plain back. 2 or 3 pen pocket on right or left sleeve with or without Velcro fastened flap. Radio bar. Zip placket with press stud fastening. Left and /or right upper chest pockets with or without Velcro or press stud fastened flap. Concealed trouser access pockets with Velcro fastening. Right and/or Left rear hip pockets with or without Velcro or press stud fastened flap. Ruler pocket on right thigh. Cargo pockets on left and /or right thigh with Velcro or press stud fastening. Cuffs with Velcro or press stud adjustable fastening. External knee pad pockets. Plain leg bottoms. Reflective tape as required.
Sizes:	XS to 2XL, leg lengths Short, Regular, Tall & Extra Tall, made to measure upon request.
Labels:	CE to IEC61482-2:2009, EN ISO11612:2015, EN1149-5:2008, EN13034:2005

Fabric:	65% FR viscose, 22% Meta-Aramid, 12% PA, 1% Antistatic Teflon Coated
Colour:	Navy Blue, Orange.
Conforms to:	EN ISO11612:2015 A1, B1, C1, EN 1149-3:2004 IEC61482-1-1:2009 (open arc) ATPV = 10.5cal/cm ² IEC61482-1-2:2007 (arc in a box) Class 1 (4KA) EN13034:2005 Type 6.
Sewing thread:	100% meta aramid.

For and on behalf of
DALE TECHNICHE LIMITED

R Pogson

Dr R. G. Pogson, Technical Manager.

