



Dale Techniche Ltd

Throstle Nest Mill, Leeds Road, Nelson, Lancashire,
England B89 7QZ. Phone: 01282 696214.

www.daledoc.co.uk
salesoffice@dale-techniche.co.uk

TECHNICAL SPECIFICATION SHEET

2 LAYER FR COVERALL - 1090NP

Garment conforms to:	Flame retardant, antistatic coverall giving protection against heat and flame. ISO11612:2015 A1,B2,C2, Protection against heat and flame. EN1149-5:2018 Discharges of static electricity.
Garment standard description:	The garment features a high collar, action pleated back, elasticated waist, covered main zip, front placket fastened by 5 covered plastic studs, covered knitted cuffs, leg bottoms with covered zip and elasticated bottom, placket with press studs covering leg zip. Radio loops to left and right chest. Non-metallic zips throughout. FR reflective tape available if required.
Sizes:	XS to 2XL, leg lengths Short, Regular, Tall & Extra Tall, made to measure upon request.
Labels:	UKCA & CE to ISO11612:2015 and EN1149-5:2018
Outer fabric:	Nomex® Comfort, woven fabric, 220 gsm, with rip stop grid. 93% Meta-Aramid, 5% Para-Aramid, 2% Antistatic.
Colour:	Navy blue.
Fabric conforms to:	EN ISO11612:2015 A1, B2, C2, EN1149-3:2004, IEC61482-1-1:2009 (open arc) ATPV = 7.8cal/cm ² , IEC 61482-1-2:2014 (arc in a box) Class 1 (4KA)
Inner fabric:	59% Protex, 39% Cotton, 2% Carbon
Colour:	Navy blue.
Fabric conforms to:	ISO11612:2015 A1, B1, EN1149-3:2004
Sewing thread:	100% meta aramid

For and on behalf of
DALE TECHNICHE LIMITED

D EMMOTT

Operations Manager.

NOMEX® is a registered trade mark of E.I. du Pont de Nemours and Company.

