

USER INFORMATION

Issue 6 Date: 07.05.2024

Garment Style: Hi Vis Coverall ARC1001/30HV



Intended Uses

In the design of this garment due respect has been paid to the basic health and safety requirements laid out in Annex II of the PPE Regulation (EU) 2016/425.

EN 61482-2 intended use:

This garment has been designed to give a specified level of protection against the thermal hazards of an electric arc flash. The fabric was tested using IEC61482-1-1:2019 'Open arc' test method and EN 61482-1-2:2014 'Box arc' test method.

The garment conforms with EN 61482-2:2020 "Live working – Protective clothing against the thermal hazards of an electric arc – Part 2: Requirements" It meets the following requirements:

ELIM – Arc Thermal Performance Value 8.1cal/cm²

EBT – Arc Thermal Performance Value 8.7cal/cm²

The fabrics used in these garments conform to IEC 61482-1-2 APC 1(4kVA). Garments have not been tested to this standard

EN 1149-5 intended use:

This garment has been designed to avoid incendiary discharges in areas where there is a risk of ignition by electrostatic discharge, including in sensitive flammable atmospheres such as Air/Hydrogen. It may not prevent discharges capable of igniting an Oxygen enriched atmosphere. This garment is not intended to give protection against mains voltages.

The garment conforms to the requirements of EN 1149-5:2018, the material having been tested to EN 1149-3:2004.

EN ISO 11612 intended use:

This garment has been designed to give a specified level of protection against accidental contact with flame and against certain forms of heat transfer.

The garment conforms with EN ISO 11612:2015 "Protective clothing — Clothing to protect against heat and flame". It meets the following requirements:

Code Letter A1 – Limited Flame Spread (Face)

Code Letter B – Convective Heat (to Level B1)

Code Letter C – Radiant Heat (to Level C1)


It is not designed to protect against molten aluminum and iron splash (Code Letters D and E).

EN ISO20471:2013 intended use.

This garment has been designed to give a specified level of protection to the torso and arms or legs to fulfill the basic safety requirements for protective clothing where conspicuity against backgrounds found in urban and rural situations is required.

The garment conforms to EN471:2013 High Visibility Warning Clothing Class 3 for area of materials and retro-reflective performance.

The use of this garment fulfills the requirements for clothing capable of signaling the user's presence visually, intended to provide conspicuity of the wearer in hazardous situations under any light conditions by day and under illumination by vehicle headlights in the dark.



EN 61482-2:2020
ELIM = 8.1cal/cm²
EBT = 8.7cal/cm²



EN 1149-5:2018
EN 1149-3:2004




EN ISO 11612:2015
A1 B1 C1



3

EN ISO20471:2013



COVERALLS/SUITS									
SIZE	XS	S	M	L	XL	2XL	3XL	4XL	5XL
CHEST (INCHES)	36"	38"	40"	42"	44"	46"	48"	50"	52"
(CM)	90cm	95cm	100cm	105cm	110cm	115cm	120cm	125cm	130cm
LEG LENGTHS AVAILABLE	SHORT	REG	TALL	XTALL					
	29"	31"	33"	35"					
TROUSERS									
WAIST (INCHES)	28"	30"	32"	34"	36"	38"	40"	42"	44"
(CM)	70cm	75cm	80cm	85cm	90cm	95cm	100cm	105cm	110cm
LEG LENGTHS AVAILABLE	SHORT	REG	TALL	XTALL					
	29"	31"	33"	35"					
JACKETS/LONG COATS									
SIZE	XS	S	M	L	XL	2XL	3XL	4XL	5XL
CHEST (INCHES)	36"	38"	40"	42"	44"	46"	48"	50"	52"
(CM)	90cm	95cm	100cm	105cm	110cm	115cm	120cm	125cm	130cm

Instructions for use:

Environmental conditions and risks at the working site shall be considered prior to the use of this garment. Deviations from the parameters in this document may result in more severe conditions;

Protective clothing shall be worn in the closed state;

Protective clothing according to this document is not intended to be used as electrical insulating protective clothing and does not provide protection against electrical shock;

Protective clothing that becomes contaminated with grease, oil, or flammable liquids or combustible materials should not be used;

Protective clothing should be cleaned when necessary;

Protective clothing that is damaged to the extent that its protective qualities are impaired (e.g. holes in the garment, not functioning closures) should not be used;

Information to the user:

Other suitable additional protective equipment (helmet and face screen, gloves with cuffs, footwear boots)) shall be used;

Other protective garments worn together with protective clothing and dirty protective clothing can reduce the protection;

Damaged garments should be repaired or replaced. in the event of tearing, such damaged clothing should not be repaired; repairing is only allowed in accordance with the manufacturer's instructions;

No undergarments or under layers should be used which melt under arc exposure, e.g. made of polyamide, polyester or acrylic fibres;

"The person wearing the electrostatic dissipative protective clothing shall be properly earthed. The resistance between the person's skin and earth shall be less than 108 Ω , e.g. by wearing adequate footwear on dissipative or conductive floors"

"Electrostatic dissipative protective clothing shall not be open or removed whilst in presence of flammable or explosive atmospheres or while handling flammable or explosive substances"

If Applicable:

"Touch and close fasteners shall not be opened when operating in hazard zones"

"Electrostatic dissipative protective clothing is intended to be worn in Zones 1, 2, 20, 21 and 22 (see EN 60079-10-1 and EN 60079-10-2) in which the minimum ignition energy of any explosive atmosphere is not less than 0,016 mJ"

"Electrostatic dissipative protective clothing shall not be used in oxygen enriched atmospheres, or in Zone 0 (see EN 60079-10-1) without prior approval of the responsible safety engineer"

"The electrostatic dissipative performance of the electrostatic dissipative protective clothing can be affected by wear and tear, laundering and possible contamination"

"Electrostatic dissipative protective clothing shall be worn in such a way that it permanently covers all non-complying materials during normal use (including bending movements)"

Earthed through contact between the main AS fabric and the skin, such as at the wearers neck and/or wrists for jackets & coveralls, or waistband for trousers.

Care Instructions



Domestic wash at 60°C
No Bleaching
Cool Iron
Can be dry cleaned
Tumble Dry (Low Heat)

Repair Instructions

Do not repair this garment using fabrics thread other than those of the same construction and flame retardant properties as used in the garment. The garment may be disposed of using normal methods for textile garments. There are no hazards from disposal by incineration or mechanical disruption.
WARNING: Tears should not be repaired by the user. Any repair made using a flammable (not flameproof) thread and or heat reactivatable fabric that is likely to melt would be very dangerous in the event of exposure to flame. **Consult the manufacturer before attempting repair**

Maintenance Instructions

Store garments in a clean and dry environment, away from direct sunlight.

Transport the garment in the package provided.

Notified Body:

Notified Body for CE marking:

Shirley® Notified Body 2895, Port Tunnel Business Park, Office 13 Unit 21, Dublin 17, ROI. performed the EU type-examination (Module B).

The items are subject to the conformity assessment procedure Module D under surveillance of Shirley®, Notified Body 2895, Port Tunnel Business Park, Office 13 Unit 21, Dublin 17, ROI.

Further information on this garment can be obtained from Dale Techniche Ltd. at the location shown at the top of this page. Certificates of Conformity can be accessed by logging on to www.daledoc.co.uk.