

TECHNICAL SPECIFICATION SHEET

SINGLE LAYER COVERALL – ARC1001/30

Garment conforms to:	Flame retardant, antistatic single layer coverall made from durable 250gsm fabric giving protection against the thermal effects of an electric arc. EN 61482-2:2020 EBT = 8.7cal/cm² ELIM 8.1cal/cm². EN ISO11612:2015 (A1, B1, C1) protection against heat and flame. EN1149-5:2018 discharges of static electricity.
Garment standard description:	The garment features a high collar, comfort pleated back, elasticated waist, and concealed 2 way main zip - placket with Velcro fastening, stretch knitted cuffs, 2 side entry pockets, adjustable concealed zip closure to leg bottom, internal knee pad pockets. Optional features – Plain back. 2 or 3 pen pocket on right or left sleeve with or without Velcro fastened flap. Radio bar. Zip placket with press stud fastening. Left and /or right upper chest pockets with or without Velcro or press stud fastened flap. Concealed trouser access pockets with Velcro fastening. Right and/or Left rear hip pockets with or without Velcro or press stud fastened flap. Ruler pocket on right thigh. Cargo pockets on left and /or right thigh with Velcro or press stud fastening. Cuffs with Velcro or press stud adjustable fastening. External knee pad pockets. Plain leg bottoms. Reflective tape as required.
Sizes:	XS to 2XL, leg lengths Short, Regular, Tall & Extra Tall, made to measure upon request.
Labels:	CE to EN61482-2:2020, EN ISO11612:2015, EN1149-5:2018,

Fabric:	65% FR viscose, 22% Meta-Aramid, 12% PA, 1% Antistatic
Colour:	Navy Blue, Orange.
Conforms to:	EN ISO11612:2015 (A1, B1, C1), EN1149-3:2004, IEC61482-1-1:2019 (open arc) EBT = 8.7cal/cm ² , ELIM 8.1cal/cm ² . EN 61482-1-2:2014 (arc in a box) Class 1 (4KA)
Sewing thread:	100% meta-aramid

For and on behalf of
DALE TECHNICHE LIMITED

D Emmott
Operations Director



Certification 2322

ISO9001