

TECHNICAL SPECIFICATION SHEET

SINGLE LAYER, FR WOVEN POLOSHIRT ARC4001

Garment conforms to:	<p>Flame retardant, antistatic polo made from durable 220gsm rip-stop fabric giving protection against the thermal effects of an electric arc.</p> <p>EN 61482-2:2020 ATPV = 7.7cal/cm² ELIM = 6.8cal/cm². EN ISO11612:2015 (A1 B1 C1) Protection against heat and flame EN1149-5:2018 Discharges of static electricity</p>
Garment standard description:	<p>The garment features include:</p> <p>Knitted collar, plain bottom and knitted cuffs.</p> <p>Options –Collar from same fabric as body. 2 or 3 pen pocket on right or left sleeve with or without Velcro fastening to flap. Radio bar. Left and /or right upper chest pockets with or without Velcro or press stud fastened flap. Cuffs with Velcro or press stud adjustable fastening.</p> <p>FR Reflective tape available if required.</p>
Sizes:	S to 2XL, Made to measure upon request.
Labels:	CE to EN61482-2:2020, EN ISO11612:2015, EN1149-5:2018.

Fabric:	Nomex® Comfort, woven fabric, 220 gsm, with rip stop grid. 93% Meta Aramid, 5% Para Aramid & 2% Antistatic.
Colour:	Navy blue – Other colours available upon request.
Conforms to:	EN ISO11612:2015 (A1, B1, C1), EN1149-3:2004, EN IEC61482-1-1:2019 (open arc) ATPV = 7.7cal/cm ² . EN IEC61482-1-1 (2.0) ELIM 6.8cal/cm ² .
Sewing thread:	100% meta aramid.

For and on behalf of
DALE TECHNICHE LIMITED

D Emmott

Operations Director.



Certification 2322
ISO9001