



USER INFORMATION

Issue 3 18.06.2020

Garment Style: Hi Vis Hoodie HXC428HV

Intended Uses

In the design of this garment due respect had been paid to the basic health and safety requirements laid out in Module B of the PPE Regulation (EU) 2016/425.



EN 1149-5:2008
 EN 1149-3:2004

EN 1149-5 intended use:

This garment has been designed to avoid incendiary discharges in areas where there is a risk of ignition by electrostatic discharge, including in sensitive flammable atmospheres such as Air/Hydrogen. It may not prevent discharges capable of igniting an Oxygen enriched atmosphere. This garment is not intended to give protection against mains voltages.

The garment conforms to the requirements of EN 1149-5:2008, the material having been tested to EN 1149-3:2004.



EN ISO 11612:2015
 A1 B1 C1

EN ISO 11612 intended use:


This garment has been designed to give a specified level of protection against accidental contact with flame and against certain forms of heat transfer.

The garment conforms to EN ISO 11612:2015 "Protective clothing — Clothing to protect against heat and flame". It meets the following requirements:

Code Letter A1 – Limited Flame Spread (Face)

Code Letter B – Convective Heat (to Level B1)

It is not designed to protect against molten aluminium and iron splash (Code Letters D and E)



EN20471:2013


X3

EN20471:2013 intended use.

This garment has been designed to give a specified level of protection to the torso and arms or legs to fulfil the basic safety requirements for protective clothing where conspicuity against backgrounds found in urban and rural situations is required.

The garment conforms to EN471:2013 High Visibility Warning Clothing Class 2.2 for area of materials and retroreflective performance.

The use of this garment fulfils the requirements for clothing capable of signalling the user's presence visually, intended to provide conspicuity of the wearer in hazardous situations under any light conditions by day and under illumination by vehicle headlights in the dark.



Standard sizes available

Chest (ins)
 XSMALL – 36
 SMALL – 38
 MEDIUM – 40
 LARGE – 42
 XLARGE – 44

XXLARGE – 46
 XXXLARGE – 48
 XXXXLARGE – 50
 XXXXXLARGE - 52

Special sizes available on request.

Warning

- The level of protection against flame will be reduced if the protective clothing is contaminated with flammable materials.
- In the event of an accidental splash of chemical or flammable liquids on this clothing, the wearer should immediately withdraw and carefully remove the protective garments, ensuring that the chemical or liquid does not come in contact with any part of the skin.
- An increase in the oxygen content of the air will reduce considerably the protection of the welders' protective clothing against flame. Care should be taken when welding in confined spaces, e.g. if it is possible that the atmosphere may become enriched with oxygen.
- The garment shall not be used in oxygen enriched atmospheres without prior approval of the responsible safety engineer
- The electrostatic dissipative performance of the electrostatic dissipative protective clothing can be affected by wear and tear, laundering and possible contamination.
- The air trapped between layers of material plays an important part in providing heat insulation. The protection is reduced in areas which are tight fitting or compressed by belt or straps. Coveralls or jacket and trousers can only provide protection if junctions between garments or with other garments at the neck, wrists and ankles is adequate.

Care Instructions



Domestic wash at 40°C
No Bleaching
Cool Iron
Tumble dry low temperature.

Repair Instructions

Do not repair this garment using fabrics thread other than those of the same construction and flame retardant properties as used in the garment. The garment may be disposed of using normal methods for textile garments, There are no hazards from disposal by incineration or mechanical disruption.

WARNING: Tears should not be repaired by the user. Any repair made using a flammable (not flameproof) thread and or heat reactivatable fabric that is likely to melt would be very dangerous in the event of exposure to flame.

Consult the manufacturer before attempting repair.

Maintenance Instructions

Store garments in a clean and dry environment, away from direct sunlight.

Transport the garment in the package provided.

Notified Body:

Notified Body No. 0338, BTTG Testing & Certification, Unit 14 Wheel Forge Way, Trafford Park, Manchester, M17 1EH, UK.