

TECHNICAL SPECIFICATION SHEET

BALACLAVA BPB925ARC

Garment conforms to:	<p>Flame retardant, antistatic open face balaclava, giving protection against the thermal effects of an electric arc made from 220g knitted fabric</p> <p>IEC61482-1-1:2009 (open arc) $E_{BT50} = 9.6\text{cal/cm}^2$ IEC61482-1-1 (2.0) ELIM = 8.2cal/cm^2 IEC61482-1-2:2007 (arc in a box) class 1 IEC61482-2-2:2009 EN1149-5:2008 (A1, B1, C1) Discharges of static electricity ISO11612:2015 Protection against heat and flame</p>
Garment standard description:	<p>The garment features:</p> <p>Single skin throughout, made from two pieces Seam over crown and down throat front.</p> <p>Rib insert around face opening, long neck.</p>
Sizes:	One Size
Label:	CE/UKCA to IEC61482 - 2:2009, ISO11612:2015, EN1149-5:2008

Fabric:	79% Meta Aramid, 5% Para aramid, 14% FR Viscose, 2% Antistatic, 220g knitted fabric
Colour:	Black
Fabric conforms to:	<p>ISO11612:2015 (A1, B1, C1) EN1149-3:2004, IEC61482-1-1:2009 (open arc) $E_{BT50} = 9.6\text{cal/cm}^2$ IEC61482-1-1 (2.0) ELIM = 8.2cal/cm^2 IEC61482-1-2:2007 (arc in a box) Class 1 (4KA)</p>
Sewing thread:	100% meta aramid.

For and on behalf of
DALE TECHNICHE LIMITED

D Emmott

Operations Manager.



Certificate number 2322/00