

TECHNICAL SPECIFICATION SHEET

BALACLAVA BPB925ARC

Garment conforms to:	Flame retardant, antistatic open face balaclava, giving protection against the thermal effects of an electric arc made from 220g knitted fabric IEC61482-1-1:2009 (open arc) E _{BT50} = 9.6cal/cm ² IEC61482-1-1 (2.0) ELIM = 8.2cal/cm ² IEC61482-1-2:2007 (arc in a box) class 1 IEC61482-2-2:2020 EN1149-5:2018 (A1, B1, C1) Discharges of static electricity ISO11612:2015 Protection against heat and flame
Garment standard description:	The garment features: Single skin throughout, made from two pieces Seam over crown and down throat front. Rib insert around face opening, long neck.
Sizes:	One Size
Label:	CE/UKCA to IEC61482-2:2020, ISO11612:2015, EN1149-5:2018

Fabric:	79% Meta Aramid, 5% Para aramid, 14% FR Viscose, 2% Antistatic, 220g knitted fabric
Colour:	Black
Fabric conforms to:	ISO11612:2015 (A1, B1, C1), EN1149-3:2004, IEC61482-1-1:2009 (open arc) E _{BT50} = 9.6cal/cm ² IEC61482-1-1 (2.0) ELIM = 8.2cal/cm ² IEC61482-1-2:2007 (arc in a box) Class 1 (4KA)
Sewing thread:	100% meta aramid.

For and on behalf of
DALE TECHNICHE LIMITED

D Emmott

Operations Manager.



Certificate number 2322/00