

Care & Usage Sheet


Issue 4 Date: 01.07.2021



PROTECTIVE TROUSERS STYLE PG3/A AND PG3/B

TECHNICAL

This garment has been designed to give a specified level of protection against accidental contact with blades and similar sharp implements. In the design of this garment due respect has been paid to the basic health and safety requirements laid out in PPE Regulation (EU) 2016/425 as brought into UK Law and amended. The garment has been tested in accordance with EN 388: 2016.

Tested in accordance with EN388:2016  X- Not tested		Level	Minimum level	Maximum level
	Abrasion resistance	2	0	4
	Blade cut resistance	X	0	5
	Tear resistance	4	0	4
	Puncture resistance	4	0	4
	TDM Cut resistance	C	A	F




Sizes – Waist 30” to 48” in 2” increments. Length – short 29”, regular 31”, long 33”.

Special sizes available on request.

Waist fit:		A	B
Inches	CM		
30"	76	153 - 190	75-79
32"	81	153 - 190	80-84
34"	86	153 - 190	85-89
36"	91	153 - 190	90-94
38"	97	153 - 190	95-99
40"	102	153 - 190	100-104
42"	107	153 - 190	105-109
44"	112	153 - 190	110-114
46"	117	153 - 190	115-119
48"	122	153 - 190	120-124

Fit according to waist size



WARNING: The garment is **CUT RESISTANT** not **CUT PROOF**. The actual conditions of use cannot be simulated and it is the responsibility of the user, not the manufacturer, to determine the garment's suitability for the intended use. The garment is sold without warranty expressed or implied. No warranty or representation is made as to the product's ability to protect the user from injury or death. The user assumes that responsibility. Do not use next to moving machinery.

USE.

These garments are for the intended use within the glass industry.

New and used garments should be thoroughly inspected before use to ensure no damage is present. **THESE GARMENTS ARE DESIGNED TO GIVE PROTECTION TO THE OUTER SIDE OF THE LEG ONLY. WHERE THERE IS ANY RISK OF CUTS TO THE INSIDE OF THE LEG THE GARMENT MUST BE WORN IN CONJUNCTION WITH A SUITABLE CUT RESISTANT APRON SUCH AS DALE TECHNICHE'S STYLE PG2/A. A SUITABLE APRON MUST BE WORN IN CONJUNCTION WITH STYLE PG3/B TROUSERS WHERE THERE IS ANY RISK TO THE UPPER LEG.**

GARMENT CARE.

The test results for the garment were achieved after 5 washes. Stored garments should be kept in their original packaging in a dry place away from heat and direct sunlight. Hand or machine wash in water not exceeding 40°C using a good proprietary washing powder or detergent. **Do not use bleach.** Line dry or dry flat. **Do not tumble dry.** The garment can be ironed with a medium iron if necessary. Failure to observe the above instructions and aggressive or repeated washing may affect the mechanical or EN388 performance of the garment.

REPAIR. Do not repair this garment.

Notified Body:

EU type examination performed by SATRA Technology Europe, Bracetown Business Park, Clonee, D15 YN2P Ireland. Notified Body number 2777.

Approved body for Type Approval: SATRA Technology Centre Ltd (AB 0321), Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, UK.

Further information on this garment can be obtained from Dale Techniche Ltd. at the location shown at the top of this page.

EU Certificates of Conformity can be accessed by logging on to www.daledoc.co.uk

REINFORCED AREAS.

PG3/A

Front

Back



Reinforced areas

PG3/B

