

Throstle Nest Mill, Leeds Road, Nelson, Lancashire, England BB9 7QZ. Phone - 01282 696214. Fax - 01282 697319 www.daledoc.co.uk - www.jaysracewear.co.uk salesoffice@dale-techniche.co.uk

USER INFORMATION

Issue 4 Date: 24.05.2021

CE


Garment: FR Beanie Hat made from Protex Cotton.



EN 1149-5:2008 EN 1149-3:2004



EN ISO 11612:2015 A1 B1 C1



Intended Uses:

In the design of this garment due respect has been paid to the basic health and safety requirements laid out in Annex II of the PPE directive (89/686/EEC).

EN 1149-5 intended use:

This garment has been designed to avoid incendiary discharges in areas where there is a risk of ignition by electrostatic discharge, including in sensitive flammable atmospheres such as Air/Hydrogen. It may not prevent discharges capable of igniting an Oxygen enriched atmosphere. This garment is not intended to give protection against mains voltages. The garment conforms to the requirements of EN 1149-5:2008, the material having been tested to EN 1149-3:2004.

EN ISO 11612:2015 intended use:

This garment has been designed to give a specified level of protection against accidental contact with flame and against certain forms of heat transfer.

The garment conforms to EN ISO 11612:2015 "Protective clothing - Clothing to protect against heat and flame". It meets the following requirements:

Code Letter A1 – Limited Flame Spread (Face).

Code Letter B - Convective Heat (to Level B1).

Code letter C – Radiant heat (to level C1).

It is not designed to protect against molten aluminium and iron splash (Code Letters D and E).

One size fits all.

Effective Use

These protective garments are to be worn with outer garments that comply with EN ISO 11612 that completely cover the upper & lower torso, neck, arms to the wrist and legs to the ankles.

For full body protection, the protective clothing shall be worn closed/fastened and other suitable PPE shall be used (helmet and face screen, gloves with cuffs, footwear). No undergarments or under layers should be used which melt under heat exposure, e.g. those made of polyamide, polyester or acrylic fibres.

The garment should not be opened or removed whilst in the presence of flammable or explosive atmospheres or while handling flammable or explosive substances. The garment is not designed to protect against electrostatic discharge.

Warning

- The level of protection against flame will be reduced if the protective clothing is contaminated with flammable materials.
- In the event of an accidental splash of chemical or flammable liquids on this clothing, the wearer should
 immediately withdraw and carefully remove the protective garments, ensuring that the chemical or liquid does not
 come in contact with any part of the skin.
- An increase in the oxygen content of the air will reduce considerably the protection of the welders' protective clothing against flame. Care should be taken when welding in confined spaces, e.g. if it is possible that the atmosphere may become enriched with oxygen.
- The garment shall not be used in oxygen enriched atmospheres without prior approval of the responsible safety engineer
- The air trapped between layers of material plays an important part in providing heat insulation. The protection is
 reduced in areas which are tight fitting or compressed by belt or straps. Coveralls or jacket and trousers can only
 provide protection if junctions between garments or with other garments at the neck, wrists and ankles is
 adequate.

Care Instructions

40

Domestic wash at 40°C No Bleaching Cool Iron Can be dry cleaned Do not tumble dry

Repair Instructions

Do not repair this garment using fabrics thread other than those of the same construction and flame retardant properties as used in the garment. The garment may be disposed of using normal methods for textile garments, There are no hazards by incineration from disposal or mechanical disruption. WARNING - Tears should not be repaired by the user. Any repair made using a flammable (not flameproof) thread and or heat reactivatable fabric that is likely to melt would be very dangerous in the event of exposure to flame. Consult the manufacturer before attempting repair

Maintenance Instructions

Store garments in a clean and dry environment, away from direct sunlight.

Transport the garment in the package provided.

Notified Body

Notified Body for CE marking:

BTTG® Notified Body 0338, BTTG, Manchester, M17 1EH, performed the EC type-examination, which is now held by Shirley®, Notified Body 2895, Port Tunnel Business Park, Office 13 Unit 21, Dublin 17, ROI.

Approved Body for UKCA marking:

BTTG® Approved Body 0338, BTTG, Manchester, M17 1EH, performed the EC type-examination for UKCA approval.

Please visit www.daledoc.co.uk for our EU Declaration of Conformity.